PR Series Order Transmittal and Check Sheet Rev Date 7/14/17 (Note: Items below listed in **bold text** are subject to additional charge if not included in original quote) Salesman: Office Phone: INFORMATION IN THIS SECTION IS REQUIRED TO VALIDATE EQUIPMENT WARRANTY Retail Distribution Bill To Address: **End User Address:** Ship To Address: **End User Type:** .com Retail Stores Aero/Auto ☐ Transportation Consumer Pharm/Medical Developer Warehouse Food/Beverage ☐ Stock ☐ Farming Government **Grocery Distribution** Technology Grocery Retail Service Industrial Entertainment PO# Requested Ship Date Shipping Instructions: Quantity Carrier □ Prepaid Flatbed Required Collect Restraint Model Quote # ☐ Van Required Comments: Phone# ☐Third Party Are lifting required for installation? ☐Yes ☐ No Leveler Size - REQUIRED Leveler Capacity - REQUIRED 25,000 lbs CIR ☐ 6'W X 6'L ☐ 6'6" W X 6'L 7'W X 6'L 45,000 lbs CIR 120,000 lbs CIR 6'W X 8'L 6'6 W X 8'L 7'W X 8'L 30,000 lbs CIR 50,000 lbs CIR ☐ 6'6" W X 10'L 7'W X 10'L 35,000 lbs CIR 60,000 lbs CIR ☐ 6'W X 10' L 6'6" W X 12'L ☐ 6' W X 12'L 7'W X 12'L ☐ 40,000 lbs CIR ■ 80,000 lbs CIR Pit Information - REQUIRED **NOTE: Pits shallower than 24" have decreased below dock service Notes: range. Consult factory for details. ☐ Existing Loading Dock Area Right Rear Right Front Pit Width Cut down in Width? Left Front Left Rear Pit Length Cut down in Length? Cut down Depth? Filler To Be Provided By Systems **Misc Metals Curb Angles Pans** Curb Angle to ship early 3 Sided Pan to ship early ☐ Date Required Date Required ☐ 6 Piece Angle ☐ 3 Sided Pan ☐ 4 Sided Pan ☐ 4 Piece Angle/ 2 piece bumper plate ☐ Squaring Kit Per Systems pit detail unless otherwise noted ■ Bumper Plate Weldments Lip/Bumper Information - REQUIRED 16" Lip ☐ Barrier Lip Max Bevel Bumpers □ 18" □ 5" ☐ Reduced Lip Crown Length: Standard is 4-1/2" x 12" x 14" □ 7" ☐ 20" If capacity is 60k, 80k, or 120k then Other 6" x 10" x 14" are standard. INFORMATION IN THIS SECTION IS REQUIRED TO VALIDATE EQUIPMENT WARRANTY Dock Height Max Gross Moving Load # of Shifts Notes: Fork ☐ 3 Wheel Required Service Range Required Service Range 4 Wheel Truck: Above **Below** 3 Wheel Offset/Standup Decline Drive % Incline Drive Level Drive If drive is decline / incline please explain how this is being handled: Electrical - Required Frame/Finish Information - Required Notes: **Electrical Voltage and Phase Cleanpit Frame** Std Auto Return to Dock **Remote Mount Powerpack Dual Lanyard Control** П **Rubber Donuts/Lip Dampners** Std Centrapower **Abrasive Deck** П # of Pump Stations **Abrasive Lip** Pump Station Voltage/Phase **Special Color Paint (Provide Sample) Smooth Deck Plate Emergency Stop Button Quick Cycle Lip (Lip Out) Smooth Lip Plate** \Box Combo Lip Out/E-Stop **Spray Metalize Disconnect Switch Hot Dip Galvanize Overhead Door Buttons**

| Optional Extras | Restraint Information | Notes: |
|-------------------------------------------------------------------------------------------------|--------------------------------------------------|---------------------|
| ☐ Brush Weatherseal (Rear Brush) | ☐ Restraint Engage Interlocking (Std) (Restraint | |
| ☐ Rubber Weatherseal (Rear Foam) | engaged or unit placed in bypass mode allows | |
| ☐ Washdown Package | leveler to operate) | |
| Includes: Rubber membrane on | Leveler Stored Interlock (Lip Prox) | |
| logic block, seal tite, Nema 4 j-box, | (Leveler stored allows restraint to be released) | |
| grease fittings, washdown motor | | |
| ☐ Insulation | Audible Alarm | |
| Stainless Steel Hinge Pins | | |
| ☐ Grease Fittings (Every Tube) | | |
| For additional loading dock, construction and safety items go to www.alliedproductsolutions.com | | |
| Additional Notes: | | Net price each: \$ |
| | | |
| | | Total net price: \$ |